

## Electronic Capacitor Blasting Machine AI2600-70/140/210



Capacitor Blasting Machine AI2600 has 3 different models to fulfill with your blasting requirements.

Lightweight, battery powered and electronically controlled, with a fast charging time and accurate precision over the energy given to the firing circuit in comparison with traditional mechanical blasting machines.

This blasting machine has been designed according to the EN-13763-26 Norm.

### Technical Data

	<b>AI-2600/70</b>	<b>AI-2600/140</b>	<b>AI-2600/210</b>
<b>Voltage</b>	2600 V / 1600 V	2600 V / 1600 V	2600 V / 1600 V
<b>Capacitor</b>	70 $\mu$ F	140 $\mu$ F	210 $\mu$ F
<b>Weight</b>	6.4 kg	7.2 kg	8.0 kg
<b>Dimensions</b>	400 x 200 x 320 mm		
<b>Test device</b>	Built-in	Built-in	Built-in
<b>Maximum resistance of the circuit</b>			
<b>Detonator type A</b> 3 mJ/ $\Omega$ Voltage: 2600 V	1.800 $\Omega$	1.800 $\Omega$	1.800 $\Omega$
<b>Detonator Type U</b> 16 mJ/ $\Omega$ Voltage: 2600 V	800 $\Omega$	825 $\Omega$	850 $\Omega$
<b>Detonator Type HU</b> 2500 mJ/ $\Omega$ Voltage: 2600 V	45 $\Omega$	60 $\Omega$	70 $\Omega$

Not valid for use in gassy mines.

Refer to the instruction manual for safety and operating mode.

The documentation described herein shall not be considered as contractual commitment.

### VIBRAQUIPO

C/ Gaiteiro de Soutelo, 3 Bajo  
36004 Pontevedra (Spain)  
Phone: (+34) 986 86 02 72  
vibraquipo@vibraquipo.com  
www.vibraquipo.com